



MODELLO TYPE		POTENZA POWER		Q	m ³ /h														
1 ~	3 ~	kW	HP		0	0.3	0.6	0.9	1.2	1.5	1.8	2.1	2.4	3.0	3.6	4.2	4.8	5.4	
				l/min	0	5	10	15	20	25	30	35	40	50	60	70	80	90	
PKm 60®	PK 60®	0.37	0.50	H (m)	40	38	33.5	29	24	19.5	15	10	5						
PKm 65	PK 65	0.50	0.70		55	50	45.5	40.5	36	31	27	22	17	8					
PKm 70	PK 70	0.60	0.85		65	62	57	52	47	42	37	32	27	18					
PKm 80	PK 80	0.75	1		70	66	61	56	51	46	41	36.5	31	22					
PKm 90	PK 90	0.75	1		90	82	71	60	49	38	27	17	5						
PKm 100	PK 100	1.1	1.5		85	80	75	70	65	60	55	50	45	35	25	15			
PKm 200	PK 200	1.5	2		90	86	81	76	71	65.5	60	55	50	40	30	20	10		
—	PK 300	2.2	3		100	95	90	85	80	75	70	65	60	50	40	30	20	10	

Q = Portata H = Prevalenza manometrica totale
 Q = Flow rate H = Total manometric head

Tolleranza delle curve di prestazione secondo EN ISO 9906 App. A.
 Tolerance of the performance curves according to EN ISO 9906 App. A.