


Technical specifications SpiroCross XC

Article number*	XC050	XC065	XC080	XC100	XC125	XC150	XC200	XC250	XC300
Connection DN [mm]	50	65	80	100	125	150	200	250	300
Connection OD [mm]	60	76	89	114	140	168	219	273	324
H [mm]	815	905	999	1261	1546	1781	2321	2870	3388
h [mm]	240	305	360	460	560	670	870	1100	1295
L [mm]	260	260	370	370	525	525	650	750	850
LF [mm]	350	350	470	475	635	635	775	890	1005
Primary Flow at 1,5 m/s [m ³ /h]	12,5	20	27	47	72	108	180	288	405
Primary Flow at 1,5 m/s [l/s]	3,5	5,5	7,5	13	20	30	50	80	113
Capacity ($\Delta T = 20^{\circ}\text{C}$) [kW]	294	462	630	1092	1680	2520	4200	6720	9450
Capacity ($\Delta T = 6^{\circ}\text{C}$) [kW]	88	139	189	328	504	756	1260	2016	2835
Volume [l]	12	13	29	38	105	123	252	501	859
Weight L [kg]	17	19	33	43	95	110	230	344	559
Weight F [kg]	26	31	49	60	119	140	274	408	643



* for weld ends add L (e.g. XC200L), for flanges add F (e.g. XC200F)