

is recommended.

Connection [DN]	Connection OD [mm]	L [mm]	LF [mm]	H [mm]	Standard; nom. 1.5 m/s							Hi-flow; nom. 3 m/s							
					Nom. = 1,5 m/s			Max. = 3 m/s				Article number*	Article number demountable*	H [mm]	Max. flow [l/s]	Max. flow [m ³ /h]	Δp at max. flow [kPa]	Article number*	Article number demountable*
					Max. flow [l/s]	Max. flow [m ³ /h]	Δp at max. flow [kPa]	Max. flow [l/s]	Max. Connection [m ³ /h]	Δp bij max. Connection [kPa]									
050	60	260	350	395	3.5	12.5	3.0	7	25	11.8	BE050	BF050	555	7	25	11.8	HE050	HF050	
065	76	260	350	395	5.5	20	2.7	11	40	11.6	BE065	BF065	555	11	40	11.6	HE065	HF065	
080	89	370	470	515	7.5	27	2.9	15	54	12.4	BE080	BF080	710	15	54	12.4	HE080	HF080	
100	114	370	475	515	13	47	3.7	26	94	14.6	BE100	BF100	710	26	94	14.6	HE100	HF100	
125	140	525	635	690	20	72	4.2	40	144	16.8	BE125	BF125	970	40	144	16.8	HE125	HF125	
150	168	525	635	690	30	108	4.9	60	215	19.4	BE150	BF150	970	60	215	19.4	HE150	HF150	
200	219	650	775	900	50	180	5.8	100	360	23.1	BE200	BF200	1240	100	360	23.1	HE200	HF200	
250	273	750	890	1145	80	288	6.9	160	575	27.7	BE250	BF250	1645	160	575	27.7	HE250	HF250	
300	324	850	1005	1360	113	405	7.7	225	810	31.0	BE300	BF300	1955	225	810	31.0	HE300	HF300	
350	356	n/a	1128	1610	140	500	7.8	280	1000	31.0	BE350	BF350	2100	280	1000	31.0	HE350	HF350	
400	406	n/a	1226	1820	180	650	8.4	360	1300	34.0	BE400	BF400	2380	360	1300	34.0	HE400	HF400	
450	457	n/a	1330	2020	235	850	10.0	470	1700	39.0	BE450	BF450	2660	470	1700	39.0	HE450	HF450	
500	508	n/a	1430	2240	295	1060	11.0	590	2120	43.0	BE500	BF500	2950	590	2120	43.0	HE500	HF500	
600	610	n/a	1630	2680	425	1530	12.0	835	3000	47.0	BE600	BF600	3530	835	3000	47.0	HE600	HF600	


Operating pressure 0 - 10 bar

Fluid temperature 0 - 110°C


Other sizes, materials, pressures and temperatures are available on request.

* for weld ends add L (e.g. BE200L)

for flanges add F (e.g. BE200F)



Standard



Hi-flow