

Spirovent deaerators specially for removing air. All products can be used for both new build projects and for renovating heating, cooling and process systems. SpiroVent deaerators are available in brass and in

suitable for a flow velocity of up to 1 m/s, can be installed in horizontal and vertical pipes. The steel models are available in standard and hi-flow designs.

www.pompa.kiev.ua

Connection	H [mm]	L [mm]	Max. flow [m ³ /h]	Max. flow [l/s]	Δp at max. flow [kPa]	Article number
22 mm. comp.	153	106	1,3	0,35	1,3	AA022
22 mm. comp. V	220	104	1,3	0,35	1,5	AA022V
G ¾	153	85	1,3	0,35	1,3	AA075
G ¾V	210	84	1,3	0,35	1,5	AA075V
G1	180	88	2,0	0,55	1,3	AA100
G1V	210	84	2,0	0,55	2,4	AA100V
G1½	200	88	3,6	1,0	1,3	AA125
G1½	234	88	5,0	1,4	1,3	AA150
G2	275	132	7,5	2,1	1,4	AA200


V= Vertical connection

Flow velocity ≤ 1 m/s

Operating pressure: 0 - 10 bar

Fluid temperature 0 - 110 °C

Other sizes, materials, pressures and temperatures are available on request



Brass, horizontal: 22 mm up to 2"



Brass, vertical: 22 mm up to 1"