



Connection [DN]	Connection OD [mm]	L [mm]	LF [mm]	H [mm]	Standard; nom. 1.5 m/s						Hi-flow; nom. 3 m/s					
					nom. = 1,5 m/s			max. = 3 m/s			Article number*	H [mm]	Max. flow [l/s]	Max. flow [m ³ /h]	Δp at max. flow [kPa]	Article number*
					Max. flow [l/s]	Max. flow [m ³ /h]	Δp at max. flow [kPa]	Max. flow [l/s]	Max. flow [m ³ /h]	Δp at max. flow [kPa]						
050	60	260	350	470	3,5	12,5	3,0	7	25	11,8	BA050	630	7	25	11,8	HA050
065	76	260	350	470	5,5	20	2,7	11	40	11,6	BA065	630	11	40	11,6	HA065
080	89	370	470	590	7,5	27	2,9	15	54	12,4	BA080	785	15	54	12,4	HA080
100	114	370	475	590	13	47	3,7	26	94	14,6	BA100	785	26	94	14,6	HA100
125	140	525	635	765	20	72	4,2	40	144	16,8	BA125	1045	40	144	16,8	HA125
150	168	525	635	765	30	108	4,9	60	215	19,4	BA150	1045	60	215	19,4	HA150
200	219	650	775	975	50	180	5,8	100	360	23,1	BA200	1315	100	360	23,1	HA200
250	273	750	890	1215	80	288	6,9	160	575	27,7	BA250	1715	160	575	27,7	HA250
300	324	850	1005	1430	113	405	7,7	225	810	31,0	BA300	2025	225	810	31,0	HA300
350	356	n/a	1128	1910	140	500	7,8	280	1000	31,0	BA350	2400	280	1000	31,0	HA350
400	406	n/a	1226	2120	180	650	8,4	360	1300	34,0	BA400	2680	360	1300	34,0	HA400
450	457	n/a	1330	2320	235	850	10,0	470	1700	39,0	BA450	2960	470	1700	39,0	HA450
500	508	n/a	1430	2540	295	1060	11,0	590	2120	43,0	BA500	3250	590	2120	43,0	HA500
600	610	n/a	1630	2980	425	1530	12,0	835	3000	47,0	BA600	3830	835	3000	47,0	HA600



Standard



Hi-flow

Operating pressure: 0 - 10 bar Fluid temperature 0 - 110 °C

Other sizes, materials, pressures and temperatures are available on request.

* for weld ends add L (e.g. HA200L)

for flanges add F (e.g. HA200F)